

## Technical Specifications: UFM 6710

Parameters	UFM 6710	
<b>Transmitter</b>		
Power supply	24 V DC $\pm$ 20% 110 V AC $\pm$ 15% 240 V AC $\pm$ 15% Solar powered	
Velocity	$\pm$ 20 m/sec. Bidirectional	
Display	2 lines, 16 characters, LCD with backlight, flow rate, velocity, totaliser	
Units	User configurable English/Metric	
Totaliser	FWD, NET, REV, BATCH (Gallons, ft <sup>3</sup> , barrels, lbs, m <sup>3</sup> )	
Output	4 - 20 mA DC Std.*	
Accuracy	$\pm$ 1% of reading @ rate > 0.5 m/sec. (Optional $\pm$ 0.5% of reading)	
Repeatability	0.2% of Span	
Protection class	IP 65, IP 67	
Dimensions	251x190x96 mm	
Weight	< 2.5 kg	
Security	Keypad lockout, access code enabled	
<b>Sensor</b>		
Suited temp. - Std.	-40°C to 120°C	
Suited temp. - High	-40°C to 250°C	
Pipe size	S Sensor	15 - 80 mm
	M Sensor	50 - 700 mm
	L Sensor	400 - 4570 mm
Dimensions	S Sensor	45x30x30 mm
	M Sensor	60x45x45 mm
	L Sensor	80x70x55 mm
Weight	S Sensor	< 0.3 kg
	M Sensor	< 0.5 kg
	L Sensor	< 1.0 kg
Protection class	IP 65, IP 67, IP 68	
Cable length	6 m std. can be extended up to 300 m	
Flexible belts	SS belt according to pipe size	
Portable case	NA	

\* For options please refer to order code from catalogue.